



Model	PG190	PG240	PG325
<b>PRIME POWER RATING</b>			
@ 480V-3Ø, 0.8PF, 60Hz	181 kVA   145 kW   218 A	235 kVA   188 kW   283 A	334 kVA   267 kW   401 A
@ 240V-3Ø, 0.8PF, 60Hz	181 kVA   145 kW   434 A	235 kVA   188 kW   566 A	334 kVA   267 kW   803 A
@ 208V-3Ø, 0.8PF, 60Hz	181 kVA   145 kW   501 A	219 kVA   175 kW   608 A	316 kVA   253 kW   877 A
@ 240V-1Ø, 1.0PF, 60Hz	110 kVA   110 kW   458 A	136 kVA   136 kW   567 A	197 kVA   197 kW   821 A
@ 120V-1Ø, 1.0PF, 60Hz	110 kVA   110 kW   458 × 2 A	136 kVA   136 kW   567 × 2 A	197 kVA   197 kW   821 × 2 A
@ 400V-3Ø, 0.8PF, 50Hz	165 kVA   132 kW   238 A	200 kVA   160 kW   289 A	280 kVA   224 kW   404 A
Voltage Configuration	3-Position Switch	Link Board Panel	Link Board Panel
Frequency Capability	50 Hz/60 Hz Switchable	50 Hz/60 Hz Switchable	50 Hz/60 Hz Switchable
<b>ENGINE</b>			
Make & Model	Cummins QSB7-G8	Cummins QSB7-G9	Cummins QSL9-G9
Displacement	6.7 L	6.7 L	8.9 L
Number of Cylinders	6	6	6
Power Output @ 1800 rpm	219 hp (163 kWm)	282 hp (210 kWm)	393 hp (293 kWm)
Emissions Tier Level	Tier 4 Final	Tier 4 Final	Tier 4 Final
Aftertreatment Technology	DOC / SCR	DOC / SCR	DOC / SCR
Usable Fuel Tank Capacity	368 gal. (1393 L)	368 gal. (1393 L)	480 gal. (1817 L)
Diesel Exhaust Fluid (DEF) Capacity	24 gal. (91 L)	24 gal. (91 L)	24 gal. (91 L)
Runtime @ 75% Load	46 hr.	36 hr.	33 hr.
<b>DIMENSIONS WITH RUNNING GEAR</b>			
Length	224.0 in. (5689 mm)	224.0 in. (5689 mm)	240.0 in. (6098 mm)
Width	83.2 in. (2114 mm)	83.2 in. (2114 mm)	83.0 in. (2109 mm)
Height	102.9 in. (2615 mm)	102.9 in. (2615 mm)	113.0 in. (2870 mm)
Weight (Ready to Run)	11,377 lb. (5172 kg)	11,377 lb. (5172 kg)	14,032 lb. (6378 kg)
Sound Level @ 23 ft. (7 m) and 100%	69 dB	69 dB	76 dB