



Model	PG400	PG570
PRIME POWER RATING		
@ 480V-3Ø, 0.8PF, 60Hz	402 kVA 322 kW 484 A	570 kVA 456 kW 686 A
@ 240V-3Ø, 0.8PF, 60Hz	402 kVA 322 kW 967 A	570 kVA 456 kW 1371 A
@ 208V-3Ø, 0.8PF, 60Hz	402 kVA 322 kW 1116 A	570 kVA 456 kW 1582 A
@ 240V-1Ø, 1.0PF, 60Hz	216 kVA 216 kW 900 A	255 kVA 255 kW 1063 A
@ 120V-1Ø, 1.0PF, 60Hz	216 kVA 216 kW 900 x 2 A	–
@ 400V-3Ø, 0.8PF, 50Hz	387 kVA 310 kW 559 A	–
Voltage Configuration	Link Board Panel	Link Board Panel
Frequency Capability	50 Hz/60 Hz Switchable	60 Hz
ENGINE		
Make & Model	Cummins QSG12	Cummins X15
Displacement	11.8 L	14.95 L
Number of Cylinders	6	6
Power Output @ 1800 rpm	475 hp (354 kWm)	680 hp (507 kWm)
Emissions Tier Level	Tier 4 Final	Tier 4 Final
Aftertreatment Technology	DOC / DPF / SCR	SCR
Usable Fuel Tank Capacity	470 gal. (1780 L)	656 gal. (2483 L)
Diesel Exhaust Fluid (DEF) Capacity	46 gal. (174 L)	46 gal. (174 L)
Runtime @ 75% Load	27 hr.	28 hr.
DIMENSIONS WITH RUNNING GEAR		
Length	241.0 in. (6121 mm)	260.0 in. (6604 mm)
Width	83.0 in. (2109 mm)	98.5 in. (2502 mm)
Height	115.0 in. (2921 mm)	119.8 in. (3043 mm)
Weight (Ready to Run)	15,450 lb. (7022 kg)	23,574 lb. (10,693 kg)
Sound Level @ 23 ft. (7 m) and 100%	76 dB	75 dB